

# 122S

**Lowry**  
The Tape Specialists



**DOUBLE COATED  
TISSUE TAPE**

## PRODUCT DESCRIPTION

This double coated tissue tape features a strong acrylic adhesive which bonds well to most surfaces and materials. Ideal for mounting small objects and can be used for bonding rubbers, foams and fabrics. Excellent for splicing and attaching applications.

## PHYSICAL PROPERTIES

Backing:	Non-Woven Tissue Paper 14 gms
Adhesive:	Acrylic Solvent
Release Liner:	Silicone and PE Coating
	155 gms/125 gms
Total Thickness:	100±5 micron
180°C Peel Strength to Steel Plate:	≥ 18 N/25 mm
Initial Tack Steel Ball 14#:	≤ 55 mm
Holding Power:	≥ 16 hours
120°C Heat Resistance:	≥ 3 minutes
Core I.D.:	3" (76mm±1)

## STANDARD WIDTHS

Custom widths available

## STANDARD LENGTHS

50 metres (164 feet)

## RECOMMENDED STORAGE CONDITIONS

The product should be stored at room temperature and be kept away from wet and/or heat source.



The above properties and results obtained refer to the average values of laboratory testing carried out on the sample Lowry® product. Lowry® does not guarantee testing accuracy and makes no guarantee of product performance, safety, or suitability, either expressed or implied, when used alone or in combination with other products. It is essential as with all pressure sensitive tapes, that the surface to which the tape is applied must be clean, dry, and free of grease and oil. Lowry® strongly urges users to undertake independent testing in order to verify the suitability of the product for whatever intended use. Lowry® assumes no responsibility for any damage or injury sustained as a result of the use of its products.