

PRODUCT DATA SHEET

WTB-PVC SERIES SOLID SURFACE & WINDOW FILM

General Product Description:

Durable calendared PVC film is tinted blue and formulated with a UV inhibitor to provide up to 12-months UV resistance on glass. Water based acrylic adhesive system is designed to maintain tack level and provide a clean easy removal from most smooth, clean surfaces. Will not creep or wrinkle after application.

Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

Product Properties:

Film:

Material	Flexible PVC Film wt UV inhibitor
Color	Blue (tinted)
UV Resistance	> 12 months Xenon weatherOmeter exposure, retaining >50% on tensile strength of film base

Film Gauge:

ASTM D-1000	3.0 mil
-------------	---------

Tensile Strength:

D882 (MD)	2250 PSI
-----------	----------

Elongation (at break):

D882 (MD)	290 %
-----------	-------

Adhesive Type:

Type	Acrylic Copolymer
Base	Water
Chemical Activity	Inert

Adhesion Properties:

PSTC-101 metal	4 oz/in
----------------	---------

Notice to Buyers:

Except as otherwise provided herein, the quality shall be in accordance with the seller's specifications. Final determination of the suitability of the use contemplated by the buyer is the SOLE RESPONSIBILITY OF THE BUYER, and the seller shall have no responsibility in connection with such suitability.