



## Safety Data Sheet

Copyright,2020, 3M Canada Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

**Document group:** 11-0058-5 **Version number:** 17.03  
**Issue Date:** 2020/10/16 **Supersedes Date:** 2019/07/08

This Safety Data Sheet has been prepared in accordance with the Canadian Hazardous Products Regulations.

### SECTION 1: Identification

#### 1.1. Product identifier

3M(TM) Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B

#### Product Identification Numbers

62-3764-7230-4	62-3764-7231-2	62-3764-7232-0	62-3764-7233-8	62-3764-7234-6
62-3764-7235-3	62-3764-7236-1	62-3764-8530-6	62-3764-9030-6	62-3764-9130-4
62-3764-9132-0	62-3764-9135-3	62-3764-9136-1	62-3764-9230-2	62-3764-9231-0
62-3764-9232-8	62-3764-9330-0	62-3764-9333-4	62-3764-9335-9	62-3764-9336-7
62-3764-9337-5	62-3764-9338-3	62-3764-9339-1	62-3764-9395-3	62-3764-9399-5
62-3764-9530-5	62-3764-9531-3	62-3764-9536-2	62-3764-9537-0	62-3764-9830-9
62-3764-9835-8	62-3764-9836-6	62-3764-9930-7		

#### 1.2. Recommended use and restrictions on use

##### Intended Use

Adhesive

##### Specific Use

hot-melt adhesive

##### Restrictions on use

Not applicable

#### 1.3. Supplier's details

**Company:** 3M Canada Company  
**Division:** Industrial Adhesives and Tapes Division  
**Address:** 1840 Oxford Street East, Post Office Box 5757, London, Ontario N6A 4T1  
**Telephone:** (800) 364-3577  
**Website:** www.3M.ca

#### 1.4. Emergency telephone number

Medical Emergency Telephone: 1-800-3M HELPS / 1-800-364-3577; Transportation Emergency Telephone (CANUTEC): (613) 996-6666

### SECTION 2: Hazard identification

**2.1. Classification of the substance or mixture**

Skin Sensitizer: Category 1A.

**2.2. Label elements**

**Signal word**

Warning

**Symbols**

Exclamation mark |

**Pictograms**



**Hazard statements**

May cause an allergic skin reaction.

**Precautionary statements**

**Prevention:**

Avoid breathing dust/fume/gas/mist/vapours/spray. Wear protective gloves. Contaminated work clothing must not be allowed out of the workplace.

**Response:**

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

**Disposal:**

Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**2.3. Other hazards**

May cause thermal burns.

7% of the mixture consists of ingredients of unknown acute oral toxicity.

7% of the mixture consists of ingredients of unknown acute dermal toxicity.

**SECTION 3: Composition/information on ingredients**

This material is a mixture.

Ingredient	C.A.S. No.	% by Wt	Common Name
Ethylene-Vinyl Acetate Polymer	24937-78-8	50 - 65	Acetic acid ethenyl ester, polymer with ethene
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	68132-00-3	15 - 40	Naphtha (petroleum), light steam-cracked, debenzenized, polymers, hydrogenated
Hydrocarbon Resin	Mixture	25 - 35	Not Applicable
Polyethylene Polymer	9006-26-2	1 - 10	2,5-Furandione, polymer with ethene
Polyolefin Wax	8002-74-2	1 - 10	Paraffin waxes and Hydrocarbon waxes

**3M(TM) Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B**

Antioxidant	6683-19-8	< 2	Benzenepropanoic acid, 3,5-bis(1,1-dimethylethyl)-4-hydroxy-, 2,2-bis[[3-[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]-1-oxopropoxy]methyl]-1,3-propanediyl ester
MALEIC ANHYDRIDE	108-31-6	0 - 0.01	2,5-Furandione

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation:**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin Contact:**

Immediately flush skin with large amounts of cold water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Cover affected area with a clean dressing. Get immediate medical attention.

**Eye Contact:**

Immediately flush eyes with large amounts of water for at least 15 minutes. DO NOT ATTEMPT TO REMOVE MOLTEN MATERIAL. Get immediate medical attention.

**If Swallowed:**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1. Information on toxicological effects.

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide  
Carbon dioxide  
Irritant Vapours or Gases

**Condition**

During Combustion  
During Combustion  
During Combustion

**5.3. Special protective actions for fire-fighters**

Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Avoid skin contact with hot material. For industrial or professional use only. Not for consumer sale or use. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse.

### 7.2. Conditions for safe storage including any incompatibilities

Store away from heat.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	C.A.S. No.	Agency	Limit type	Additional Comments
MALEIC ANHYDRIDE	108-31-6	ACGIH	TWA(inhalable fraction and vapor):0.01 mg/m3;TWA:0.01 mg/m3	Dermal/Respiratory Sensitizer, Sensitizer
Polyolefin Wax	8002-74-2	ACGIH	TWA(as fume):2 mg/m3	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

CEIL: Ceiling

### 8.2. Exposure controls

#### 8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

#### 8.2.2. Personal protective equipment (PPE)

##### Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full Face Shield

Indirect Vented Goggles

##### Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions.

**3M(TM) Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B**

Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing.

Gloves made from the following material(s) are recommended: Butyl Rubber

Fluoroelastomer

Nitrile Rubber

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron – Butyl rubber

Apron – Nitrile

**Respiratory protection**

None required.

**Thermal hazards**

Wear heat insulating gloves when handling hot material to prevent thermal burns.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Solid
<b>Specific Physical Form:</b>	Waxy Solid
<b>Colour</b>	White
<b>Odour</b>	Odourless
<b>Odour threshold</b>	<i>No Data Available</i>
<b>pH</b>	<i>Not Applicable</i>
<b>Melting point/Freezing point</b>	<i>No Data Available</i>
<b>Boiling point</b>	<i>Not Applicable</i>
<b>Flash Point</b>	267.8 °C [Test Method:Cleveland Open Cup] [Details:CONDITIONS: ASTM D-92-72]
<b>Evaporation rate</b>	<i>Not Applicable</i>
<b>Flammability (solid, gas)</b>	Not Classified
<b>Flammable Limits(LEL)</b>	<i>Not Applicable</i>
<b>Flammable Limits(UEL)</b>	<i>Not Applicable</i>
<b>Vapour Pressure</b>	<i>Not Applicable</i>
<b>Viscosity/Kinematic Viscosity      Viscosity/Kinematic Viscosity</b>	<i>Not Applicable</i>
<b>Density</b>	0.95 g/cm <sup>3</sup>
<b>Relative density</b>	0.95 [Ref Std:WATER=1]
<b>Water solubility</b>	Nil
<b>Solubility- non-water</b>	<i>No Data Available</i>
<b>Partition coefficient: n-octanol/ water</b>	<i>No Data Available</i>
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Decomposition temperature</b>	<i>No Data Available</i>
<b>Viscosity/Kinematic Viscosity</b>	<i>Not Applicable</i>
<b>Volatile Organic Compounds</b>	0 g/l [Test Method:calculated SCAQMD rule 443.1]
<b>Percent volatile</b>	0 % weight
<b>VOC Less H<sub>2</sub>O &amp; Exempt Solvents</b>	0 g/l [Test Method:calculated SCAQMD rule 443.1]
<b>Molecular weight</b>	<i>No Data Available</i>
<b>Solids Content</b>	100 %

**Nanoparticles**

This material does not contain nanoparticles.

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

This material is considered to be non reactive under normal use conditions.

### 10.2. Chemical stability

Stable.

### 10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

### 10.4. Conditions to avoid

None known.

### 10.5. Incompatible materials

None known.

### 10.6. Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
------------------	------------------

None known.

Refer to section 5.2 for hazardous decomposition products during combustion.

## SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labeling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

### 11.1. Information on Toxicological effects

#### Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

#### Inhalation:

No health effects are expected.

#### Skin Contact:

During heating:

Thermal Burns: Signs/symptoms may include intense pain, redness and swelling, and tissue destruction.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

#### Eye Contact:

During heating:

Thermal Burns: Signs/symptoms may include severe pain, redness and swelling, and tissue destruction.

#### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

#### Toxicological Data

**3M(TM) Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Ethylene-Vinyl Acetate Polymer	Dermal		LD50 estimated to be > 5,000 mg/kg
Ethylene-Vinyl Acetate Polymer	Ingestion	Rat	LD50 > 1,000 mg/kg
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Dermal		LD50 estimated to be > 5,000 mg/kg
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Ingestion		LD50 estimated to be > 5,000 mg/kg
Hydrocarbon Resin	Dermal	Rat	LD50 > 2,000 mg/kg
Hydrocarbon Resin	Ingestion	Rat	LD50 > 5,000 mg/kg
Polyethylene Polymer	Dermal	Rabbit	LD50 > 7,940 mg/kg
Polyethylene Polymer	Ingestion	Rat	LD50 > 10,000 mg/kg
Polyolefin Wax	Dermal	Rat	LD50 > 5,000 mg/kg
Polyolefin Wax	Ingestion	Rat	LD50 > 5,000 mg/kg
Antioxidant	Dermal	Rabbit	LD50 > 3,160 mg/kg
Antioxidant	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 1.95 mg/l
Antioxidant	Ingestion	Rat	LD50 > 10,250 mg/kg
MALEIC ANHYDRIDE	Dermal	Rabbit	LD50 2,620 mg/kg
MALEIC ANHYDRIDE	Ingestion	Rat	LD50 1,030 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Ethylene-Vinyl Acetate Polymer	Professional judgment	No significant irritation
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Professional judgment	No significant irritation
Polyethylene Polymer	Rabbit	No significant irritation
Polyolefin Wax	Rabbit	No significant irritation
Antioxidant	Rabbit	No significant irritation
MALEIC ANHYDRIDE	Human and animal	Corrosive

**Serious Eye Damage/Irritation**

Name	Species	Value
Ethylene-Vinyl Acetate Polymer	Professional judgment	No significant irritation
NAPHTHA (PETROLEUM), LIGHT STEAM-CRACKED, DEBENZENIZED, POLYMERS, HYDROGENATED	Professional judgment	No significant irritation
Polyethylene Polymer	Rabbit	Mild irritant
Polyolefin Wax	Rabbit	No significant irritation
Antioxidant	Rabbit	Mild irritant
MALEIC ANHYDRIDE	Rabbit	Corrosive

**Skin Sensitization**

**3M(TM) Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B**

Name	Species	Value
Polyolefin Wax	Guinea pig	Not classified
Antioxidant	Human and animal	Not classified
MALEIC ANHYDRIDE	Multiple animal species	Sensitizing

**Respiratory Sensitization**

Name	Species	Value
MALEIC ANHYDRIDE	Human	Sensitizing

**Germ Cell Mutagenicity**

Name	Route	Value
Polyolefin Wax	In Vitro	Not mutagenic
Antioxidant	In Vitro	Not mutagenic
Antioxidant	In vivo	Not mutagenic
MALEIC ANHYDRIDE	In vivo	Not mutagenic
MALEIC ANHYDRIDE	In Vitro	Some positive data exist, but the data are not sufficient for classification

**Carcinogenicity**

Name	Route	Species	Value
Polyolefin Wax	Ingestion	Rat	Not carcinogenic
Antioxidant	Ingestion	Multiple animal species	Not carcinogenic

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Antioxidant	Ingestion	Not classified for female reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Antioxidant	Ingestion	Not classified for male reproduction	Rat	NOAEL 688 mg/kg/day	2 generation
Antioxidant	Ingestion	Not classified for development	Multiple animal species	NOAEL 1,000 mg/kg/day	during organogenesis
MALEIC ANHYDRIDE	Ingestion	Not classified for female reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for male reproduction	Rat	NOAEL 55 mg/kg/day	2 generation
MALEIC ANHYDRIDE	Ingestion	Not classified for development	Rat	NOAEL 140 mg/kg/day	during organogenesis

**Target Organ(s)****Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
MALEIC ANHYDRIDE	Inhalation	respiratory irritation	May cause respiratory irritation	Human	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
------	-------	-----------------	-------	---------	-------------	-------------------

**3M(TM) Hot Melt Adhesive 3764-AE, 3764-PG, 3764-TC, 3764-Q, 3764-B**

Ethylene-Vinyl Acetate Polymer	Ingestion	liver	Not classified	Rat	NOAEL 4,000 mg/kg/day	90 days
Polyolefin Wax	Ingestion	heart	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 15 mg/kg/day	90 days
Polyolefin Wax	Ingestion	hematopoietic system   liver   immune system   skin   endocrine system   bone, teeth, nails, and/or hair   muscles   nervous system   eyes   kidney and/or bladder   respiratory system   vascular system	Not classified	Rat	NOAEL 1,500 mg/kg/day	90 days
Antioxidant	Ingestion	endocrine system	Not classified	Rat	NOAEL 450 mg/kg/day	2 years
Antioxidant	Ingestion	liver	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
Antioxidant	Ingestion	hematopoietic system   nervous system   kidney and/or bladder	Not classified	Rat	NOAEL 2,500 mg/kg/day	90 days
Antioxidant	Ingestion	auditory system   eyes	Not classified	Dog	NOAEL 302 mg/kg/day	90 days
MALEIC ANHYDRIDE	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	LOAEL 0.0011 mg/l	6 months
MALEIC ANHYDRIDE	Inhalation	endocrine system   hematopoietic system   nervous system   kidney and/or bladder   heart   liver   eyes	Not classified	Rat	NOAEL 0.0098 mg/l	6 months
MALEIC ANHYDRIDE	Ingestion	kidney and/or bladder	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 55 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	liver	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 250 mg/kg/day	183 days
MALEIC ANHYDRIDE	Ingestion	heart   nervous system	Not classified	Rat	NOAEL 600 mg/kg/day	183 days
MALEIC ANHYDRIDE	Ingestion	gastrointestinal tract	Not classified	Rat	NOAEL 150 mg/kg/day	80 days
MALEIC ANHYDRIDE	Ingestion	hematopoietic system	Not classified	Dog	NOAEL 60 mg/kg/day	90 days
MALEIC ANHYDRIDE	Ingestion	skin   endocrine system   immune system   eyes   respiratory system	Not classified	Rat	NOAEL 150 mg/kg/day	80 days

**Aspiration Hazard**

For the component/components, either no data are currently available or the data are not sufficient for classification.

**Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.**

**SECTION 12: Ecological information**

No data available.

**SECTION 13: Disposal considerations**

### 13.1. Disposal methods

Dispose of contents/ container in accordance with the local/regional/national/international regulations.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

## **SECTION 14: Transport Information**

Not regulated per U.S. DOT, IATA or IMO.

These transportation classifications are provided as a customer service. As the shipper YOU remain responsible for complying with all applicable laws and regulations, including proper transportation classification and packaging. 3M's transportation classifications are based on product formulation, packaging, 3M policies and 3M's understanding of applicable current regulations. 3M does not guarantee the accuracy of this classification information. This information applies only to transportation classification and not the packaging, labeling, or marking requirements. The original 3M package is certified for Canadian ground shipment only. If you are shipping by air or ocean, the package may not meet applicable regulatory requirements.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Japan Chemical Substance Control Law. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Philippines RA 6969 requirements. Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

## **SECTION 16: Other information**

**National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.**

**Health: 2 Flammability: 1 Instability: 0 Special Hazards: None**

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include

the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

<b>Document group:</b>	11-0058-5	<b>Version number:</b>	17.03
<b>Issue Date:</b>	2020/10/16	<b>Supersedes Date:</b>	2019/07/08

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date issued. The manufacturer **MAKES NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY IMPLIED WARRANTY OR CONDITION ARISING OUT OF A COURSE OF PERFORMANCE, COURSE OF DEALING, CUSTOM OR USAGE OF TRADE.** User is responsible for determining whether the product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

**3M Canada SDSs are available at [www.3M.ca](http://www.3M.ca)**